


Table 8 — Flange facing dimensions

DN	d_1												f_1	f_2	f_3	f_4	W^b	x	y	z^b	$\alpha \approx$	R					
	PN 2,5 ^a	PN 6 ^a	PN 10	PN 16	PN 25	PN 40	PN 63	PN 100	PN 160	PN 250	PN 320	PN 400															
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm		mm						
10	35	35	40	40	40	40	40	40	40	40	40	40	2	4,5	4,0	2,0	24	34	35	23	—	2,5					
15	40	40	45	45	45	45	45	45	45	45	45	45					29	39	40	28	—						
20	50	50	58	58	58	58	58	58	58	58	58	58					36	50	51	35	41°						
25	60	60	68	68	68	68	68	68	68	68	68	68					43	57	58	42							
32	70	70	78	78	78	78	78	78	78	78	78	78					51	65	66	50							
40	80	80	88	88	88	88	88	88	88	88	88	88					61	75	76	60							
50	90	90	102	102	102	102	102	102	102	102	102	102	73				87	88	72								
65	110	110	122	122	122	122	122	122	122	122	122	122	95				109	110	94								
80	128	128	138	138	138	138	138	138	138	138	138	138	106				120	121	105								
100	148	148	158	158	162	162	162	162	162	162	162	162	129				149	150	128	32°			3				
125	178	178	188	188	188	188	188	188	188	188	188	188	155	175	176	154											
150	202	202	212	212	218	218	218	218	218	218	218	218	183	203	204	182											
200	258	258	268	268	278	285	285	285	285	285	285	285	239	259	260	238											
250	312	312	320	320	335	345	345	345	345	345	345	—	292	312	313	291											
300	365	365	370	378	395	410	410	410	410	—	—	—	343	363	364	342											
350	415	415	430	438	450	465	465	465	—	—	—	—	4	5,5	5,0	3,0	395	421	422	394	27°	3,5					
400	465	465	482	490	505	535	535	535	—	—	—	—					447	473	474	446							
450	520	520	532	550	555	560	560	560	—	—	—	—					497	523	524	496							
500	570	570	585	610	615	615	615	615	—	—	—	—					549	575	576	548							
600	670	670	685	725	720	735	735	—	—	—	—	—					649	675	676	648							
700	775	775	800	795	820	840	840	—	—	—	—	—					751	777	778	750							
800	880	880	905	900	930	960	960	—	—	—	—	—	856				882	883	855								
900	980	980	1 005	1 000	1 030	1 070	1 070	—	—	—	—	—	961				987	988	960								
1 000	1 080	1 080	1 110	1 115	1 140	1 180	1 180	—	—	—	—	—	5				6,5	6,0	4,0	1 062			1 092	1 094	1 060	28°	4
1 200	1 280	1 295	1 330	1 330	1 350	1 380	1 380	—	—	—	—	—								1 262			1 292	1 294	1 260		
1 400	1 480	1 510	1 535	1 530	1 560	1 600	—	—	—	—	—	—		1 462	1 492	1 494				1 460							
1 600	1 690	1 710	1 760	1 750	1 780	1 815	—	—	—	—	—	—		1 662	1 692	1 694				1 660							
1 800	1 890	1 920	1 960	1 950	1 985	—	—	—	—	—	—	—		1 862	1 892	1 894				1 860							
2 000	2 090	2 125	2 170	2 150	2 210	—	—	—	—	—	—	—		2 062	2 092	2 094				2 060							
2 200	2 295	2 335	2 370	—	—	—	—	—	—	—	—	—		—	—	—				—							
2 400	2 495	2 545	2 570	—	—	—	—	—	—	—	—	—		—	—	—				—							
2 600	2 695	2 750	2 780	—	—	—	—	—	—	—	—	—		—	—	—				—							
2 800	2 910	2 960	3 000	—	—	—	—	—	—	—	—	—		—	—	—				—							
3 000	3 110	3 160	3 210	—	—	—	—	—	—	—	—	—	—	—	—	—											
3 200	3 310	3 370	—	—	—	—	—	—	—	—	—	—	—	—	—	—											
3 400	3 510	3 580	—	—	—	—	—	—	—	—	—	—	—	—	—	—											
3 600	3 720	3 790	—	—	—	—	—	—	—	—	—	—	—	—	—	—											
3 800	3 920	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—											
4 000	4 120	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—											

Type B: Raised face (B1 and B2)



Type B: Raised face (B1 and B2)

^a Flange facing types C, D, E, F, G and H according to Figure 4 are not used for PN 2,5 and 6.

^b Flange facing types G and H according to Figure 4 are only used for PN 10 to PN 40.